



# Specifications for Tyres (Hi-Ace Van)

Department	MEASUREMENT -TRANSMISSION	Section	Gas Quality
Description	Tyre For Hiace Van		
Spec #	Meas. KT/Tyre For Hiace Van/ 02-2026		

## 1. General Requirements

- 1.1. The tyre shall be a Light Truck Radial (LTR) tyre specially designed for use on commercial vans.
- 1.2. The tyre shall feature a non-directional rib-type tread suitable for both front and rear axle usage.
- 1.3. The tyre shall have specifically designed grooves to enhance wet traction.
- 1.4. The tyre shall have a reinforced heavy-duty casing resistant to impact, cuts, and nail penetration.

## 2. Design and Dimensions

- 2.1. Tyre Dimensions:
  - 2.1.1. Overall Diameter 690 mm  $\pm$  5 mm
  - 2.1.2. Overall Section Width 195  $\pm$  5 mm
  - 2.1.3. Aspect Ratio 80
  - 2.1.4. Rim Compatibility R15
- 2.2. The tyre shall be capable of supporting a load capacity of 1000  $\pm$  30kg or above.
- 2.3. The tyre shall have 8 ply rating (8PR) to ensure adequate structural strength.

## 3. Compliance & Documentation

- 3.1. Supplier must provide:
  - 3.1.1. OEM supporting literature/datasheet for the offered tyre model
  - 3.1.2. Warranty documentation, valid for a minimum of 1 year.
- 3.2. All supplied tyres shall be brand-new, and the manufacturing date must not exceed 6 months at the time of delivery.
- 3.3. Country of Origin: US / Europe / Japan.

## 4. Delivery Period

- 4.1. The supplier is required to deliver the material within 21 days after the issuance of PO.

Prepared By	Checked By	Approved By
-------------	------------	-------------