

LT Drill Machine
Technical Specifications

Input Power	780-850 Watt
Frequency	50 Hz
Voltage	220-240V
No-load speed	1100~1200 rpm
Impact Speed	4500~ 4600 bpm
Function	Drilling, Hammer Drilling, and Chiseling
Drill and Chisel	03 drills and 02 chisels
Drill Type	Rotary Drill
Max. drilling capacity	Concrete:26mm Steel:13mm Wood:30~32mm
Tool compatible	Brick, Ceramic, Concrete, Drywall, Fiber Glass, Limestone, Marble, Masonry, Metal, Plastic, Stone, Tile, Wood
Power Tool Feature	SDS-Plus to Keyless Chuck Adapter, Lock Switch, Reverse/Forward



Portable De-watering Pump
Technical Specifications

Pump Type	Self-Priming Centrifugal Surface Pump
Motor Power	2 HP
Supply Voltage	220-240 VAC, Single Phase
Frequency	50 Hz
Current	6 to 9 A
Motor Speed	2900 RPM
Suction Lift	6 to 7m
Total Head	18 to 30m
Flow Rate	250~ 320 L/min
Protection Class	IP55
Insulation Class	Class F
Thermal Protection	Built-in Thermal Overload Protector
Pump Body	Cast Iron
Motor Housing	Cast Iron / Aluminum
Impeller	Stainless Steel 304 or Cast Iron
Shaft	Stainless Steel (SS304/SS410)
Suction Pipe Size	2" (50 mm)
Discharge Pipe Size	2" (50 mm)
Heavy Duty Hose Pipe	2"



Special Terms and Conditions

1. The bidder must submit detailed technical literature along with the bid.
2. The quoted item should be of reputable brand.
3. The bidder may be asked to submit sample (if required) for necessary technical evaluation.
4. The schedule of supply of material is 30-45 days after the issuance of Purchase Order (PO).
5. Point of Contact/ Focal Persons:

Ms. Summaira
Engineer (Electrical)
Services Department, Head Office

Cell: +92-320-6868910
Email: summaira.aslam@ssgc.com.pk

Mr. Attaullah Arbab
Chief Engineer (Electrical)
Services Department, Head
Office
Cell: +92- 3228214530
Email:
attaullah.arbab@ssgc.com.pk

